

Speed Dryer

Code: P.101.xxx

Usage

For drying paper or pulp sheets or for mass determination of sludge.

Applicable standards

- TAPPI T205





Control panel with digital display



Speed dryer 900 x 400 mm

Device description

The speed dryer is a sturdy device with a stainless steel housing which is surrounding the aluminum heating plate. The housing prevents from touching the heating plate from any side. The light weight cover is stringed with a special fabric that hold the sheets down to the drying plate and prevents them from warping. The maximum temperature is 180°C. There are four different sizes available. The largest plate can hold up to 6 standard TAPPI hand-sheets at once.

Delivery content

- speed dryer with connection cable
- spare cloth
- 2 additional fuses (3,15 A and 12,5 A)
- user manual

Specifications

- top quality and manufacturing
- stainless steel housing
- special heating plate with equal heat distribution
- lightweight drying cover
- ON/OFF switch in the front of the device
- adjustable temperature (up to 180°C ± 1°C max deviation)
- special air permeable fabric for perfect steam evaporation
- easy changeable spare cloth

Connections

- Electricity: 110 - 240 V, 50/60 Hz AC

Models

Code	Size	Dimensions	Weight	Power 230 V
P.101.350	350 x 350 mm	385 x 485 x 190 mm	17 kg	2000 W
P.101.480	480 x 480 mm	513 x 600 x 190 mm	30 kg	2400 W
P.101.580	580 x 430 mm	615 x 565 x 190 mm	34 kg	2400 W
P.101.900	900 x 400 mm	935 x 535 x 190 mm	50 kg	3200 W