

Luminous Table

Code: D.806.xxx

Usage

To visually examine dirt and shives in paper and board samples by transmitted light.

Applicable standards

- ISO 5350

Device description

This light table permits not only classical transparency and film viewing, but also quality control of translucent copy under a D50 standard illuminant. The color-neutral, anti-reflective surface and special reflectors ensure homogeneous illumination with high luminous efficiency. The light table is continuously dimmable between 500 and 5 000 lux. The working height is adjustable from 80 to 95 cm to suit your personal needs and the luminous plate can be tilted from 0 – 85° for an ergonomic working process.



Specifications

- robust and ergonomic design
- color-neutral, anti-reflective surface
- special reflectors for homogeneous illumination with high luminous efficiency
- continuously dimmable: 500 – 5 000 lux
- working height adjustable: 80 – 95 cm
- luminous plate tiltable: 0 – 85°
- luminous density: 2 500 – 3 000 cd/m²
- illumination: 9 x 36 watts / 5 000 Kelvin
- quick-start button, easy on eyes, flicker-free
- illumination area: 116 x 93 cm (W x D)

Connections

- Electricity: 230 V, 50 Hz AC

Delivery content

- illuminous plate & mounting table
- connection cable
- dirt estimation chart acc. ISO 5350-1
- user manual

Models

Code	Article
D.806.200	Luminous table with dimming knob
D.806.300	Luminous table with digital control display
Customized options are available. For more information contact your personal distributor or PTE Austria directly.	